BOMBARADI

ottoman® BY ENESCO

Bombaradi 04

Bombaradi 03

Bombaradi 06

Projects

Bombaradi 02

Bombaradi 06

Projects

Bombaradi 02

Bombaradi 02 & Melodia 09,47

Colors









Specifications

Style Name:	Bombaradi
Construction:	Level Loop
Fiber:	Nylon
Gauge:	1/10″
Stitches:	11 per inch
Average Pile Height:	3mm±0.5mm
Backing:	EcoAce-Bac ®
Tile size:	50cm*50cm
Traffic Classification:	Class II – Heavy Commercial
Antimicrobial:	Ultra-Fresh Treatment (Available)
Flammability:	ASTM E 648 Class I, GB8624-2012 B1(C)
Smoke Density:	ASTM E 662 Less than 450, GB/T 8627-1999
Static Propensity:	AATCC-134 ≤3.5kV, GB/T 18044-2008

Monolithic

Quarter-turn

Brick

Ashlar

Non-directional

GREEN LABEL +PLUS™
INDOOR AIR QUALITY CARPET TESTING PROGRAM
ID No.: GLP 6331
The Carpet and Rug Institute
carpet-rug.org

CERTIFIED
ENVIRONMENTAL PRODUCT DECLARATION

Published HPD
Health Product Declaration™ Collaborative

OHSAS18001:2007

ISO9001:2008

ISO14001:2004

LIVING BUILDING CHALLENGE

LEED

WELL

Declare.