

# OMNI SPORT



- Sport Vinyl Flooring



FOREST GREEN



FIELT GREEN



MAPLE



ROYAL BLUE



SKY BLUE



ORANGE

## OMNI-SPORT



TECHNICAL CHARACTERISTICS			
Test Items	Test Method	SPEED -3,45mm	REFERENCE-6,5mm
Wear layer thickness	EN ISO 24340	0,70 mm	0,70 mm
Total thickness	EN ISO 24346	3,45 mm	6,5 mm
Total weight	EN ISO 23997	3040 g/m <sup>2</sup>	3040 g/m <sup>2</sup>
Total kilo/m2	-	3300 kg/m <sup>2</sup>	4710 kg/m <sup>2</sup>
Performance Declaration No.	EN 14041	0120-006DoP-2013-04	0120-006DoP-2013-04
Fire resistance	EN ISO 13501-1	Cfl-s1	Cfl-s1
Static Electricity Tendency	EN 1815	antistatic (≤ 2 kV)	antistatic (≤ 2 kV)
Thermal Resistance	EN ISO 10456	0,050 m <sup>2</sup> •K/W	0,050 m <sup>2</sup> •K/W
Slip Resistance	EN 13893	Class DS (μ ≥ 0,30)	Class DS (μ ≥ 0,30)
Permanent Stinging	EN ISO 24343-1	≤ 0,18 mm	≤ 0,18 mm
Dimensional Stability	EN ISO 23999	average measured value : ≤ 0.10 %	average measured value : ≤ 0.10 %
Color fastness to light	EN ISO 105-B02	≥ 6	≥ 6
Impact sound insulation - ΔLw	EN ISO 717/2	20 dB	20 dB
Reducing in-room impact noise	NF S31-074	A Class (≤ 65 dB)	A Class (≤ 65 dB)
Heat Curl Resistance	EN ISO 23999	≤  8  mm	≤  8  mm
Phthalate Content	-	100% Phthalate-free	100% Phthalate-free
Total VOC emissions	EN 16516	Platinum (≤ 10 μg/m <sup>3</sup> )	Platinum (≤ 10 μg/m <sup>3</sup> )
Formaldehyde Emission	EN 717-1	E1	E1

