

NEW CLASSICCO

ottoman[®]
BY ENESCO
















Specifications


Style Name: Bava Rio / Gunes / To-Sorento / Study
Construction: Multi-level Loop
Fiber: Universal Nylon 66
Gauge: 1/12"
Stitches: 11 per inch
Average Pile Height: 4mm±0.5mm
Backing: EcoAce-Bac®
Tile size: 50cm*50cm
Area of Use: Commercial - Heavy Duty
Antimicrobial: Ultra-Fresh Treatment (Available)
Flammability: ASTM E 648 Class I, GB8624-2012 B1(C)
Smoke Density: ASTM E 662 Less than 450, GB/T 8627-1999
Static Propensity: AATCC-134 ≤3.5kV, GB/T 18044-2008




Style Name: Gunes
Construction: Multi-level Loop
Fiber: Nylon
Gauge: 1/12"
Stitches: 10 per inch
Average Pile Height: 3.5mm±0.5mm
Backing: EcoAce-Bac®
Tile size: 50cm*50cm
Area of Use: Commercial - Heavy Duty
Antimicrobial: Ultra-Fresh Treatment (Available)
Flammability: ASTM E 648 Class I, GB8624-2012 B1(C)
Smoke Density: ASTM E 662 Less than 450, GB/T 8627-1999
Static Propensity: AATCC-134 ≤3.5kV, GB/T 18044-2008



Monolithic



Quarter-turn



Brick



Ultra-Fresh is a registered trademark of Thomson Research Associates, Inc.