

Tasless





Tasless 02








Tasless 03



Tasless 05

Tasless Specification Sheet

Reference picture:	
Fiber:	100% Polypropylene
Structure:	Loop pile: Multi-Level loop
Gauge:	1/12"
Stitches:	10 per inch
Tufts/sqm:	186000
Average Pile Height:	4.0+/-0.5mm
Total Height:	6.3+/-0.5mm
Pile Weight:	750g/sqm
Total Weight:	3500g/sqm
Tile Size:	25*100cm
Backing:	E+Bac
Approved Installation Method:	  Herringbone Ashlar
Flammability:	ASTM E 645: ≥ 0.22 watts/cm ² Class II
Smoke Density:	ASTM E 662: ≤ 450 DMC
Dimensional Stability	AACHEN: ≤ 0.2 %
Tuft Bind:	ASTM D 1335: ≥ 8.0 lbs
Delamination:	ASTM D 3936: ≥ 3.0 lbc/in
Static Propensity	AATCC 134: ≤ 3.5 kV
Colorfastness to Light	AATCC 16E: $\geq 4-5$
Colorfastness to Water	AATCC 107: $\geq 4-5$
Colorfastness to Crocking	AATCC 165: $\geq 4-5$





TASLESS 01



TASLESS 02



TASLESS 03



TASLESS 04



TASLESS 05



TASLESS 06

ottoman[®]
BY ENESCO

AF Com Center, Samed Vurgun Küçesi No.60 Nesimi
BAKU AZ1014 AZERBAJCAN
+994 12 5966030 +994 50 2503366
info@ottoman.az
www.ottoman.az

E F.S.M Mahallesi. Yeşil Vadi Konakları F/61
Ümraniye / İstanbul 34771 TÜRKİYE
+90 216 6502250 +90 541 3777671
info@enesco.com.t
www.enesco.com.tr